

Model ESSE-12

eSENSE II™

Carbon dioxide transmitter

PRODUCT DESCRIPTION

eSENSE™ II is a new simple, low cost, state-of-the-art, infrared and maintenance-free carbon dioxide transmitter for installation in the climate zone or in the ventilation duct.

eSENSE™ II measures the carbon dioxide concentration in the ambient air up to 2000 ppm and transforms the data into an analogue output.

eSENSE™ II helps you de-creasing your energy consumption while creating a healthier indoor climate!



FEATURES

- Measurement range: 0 - 2 000 ppm CO₂
- Two analogue outputs (not model -I):
- Internal automatic self-diagnostics.
- Maintenance-free in normal applications
- Cost-optimized for connection to DDC's
- Prepared for complementary passive temperature element (model -Tr).

APPLICATIONS

eSENSE™ is an extremely cost-optimized sensor solution for climate control of buildings and other processes.

By controlling the ventilation based on actual demand, it helps you decrease your energy consumption and yet have a healthy indoor climate!

The different housing options makes the eSENSE™ available to almost any application or environment for example in greenhouses, residential and commercial buildings.

eSENSE™ -Tr is also prepared for quick mounting of a complementary passive temperature element, which can easily be done by the customer.

eSENSE™ II has a new housing that fits directly on top of EU and US electrical junction box standards



General Performance

| | |
|-----------------------------------|--|
| Compliance with | EMC directive 89/336/EEC. RoHS directive 2002/95/EG |
| Operating Temperature Range | 0 - 50 °C |
| Storage Temperature Range | -40 to +70 °C (display model -D: -20 to +70 °C) |
| Operating Humidity Range | 0 to 95% RH (non-condensing) |
| Operating Environment | residential, commercial and industrial spaces ¹ |
| Warm-up Time | ≤ 1 min. (@ full specs ≤ 15 minutes) |
| Sensor Life Expectancy | > 15 years |
| Maintenance Interval | no maintenance required ² |
| Self Diagnostics | complete function-check, LCD error indication (display model -D) |
| Display (model -D) | 4 Digits, 7 segments LCD with ppm indicator |

Electrical

| | |
|-----------------------------------|---|
| Power Input | 24 VAC/VDC ±20%, 50 Hz (half-wave rectifier input) |
| Power Consumption | < 1 Watt average |
| Connection screw terminal A | 4 x 1,5 mm ² for power input (G+, G0) and voltage outputs (OUT1, OUT2) |
| Connection screw terminal B | 2 x 1,5 mm ² for passive resistive output (Y, M) for option -Tr |

CO₂ Measurement

| | |
|---|--|
| Sensing method | Gold-plated infrared (NDIR) waveguide technology with Automatic Background Calibration (ABC) and passive gas diffusion (no moving parts) |
| Response Time (T _{1/e}) | < 10 sec. @ 30 cc/min. flow rate , < 3 min. diffusion time |
| Repeatability | ± 20 ppm ± 1 % of reading |
| Accuracy ² | ± 30 ppm ± 3 % of reading |
| Annual Zero Drift ² | < ± 10 ppm |
| Pressure Dependence | + 1.6 % reading per kPa |
| Measurement range | 0 - 3 000 ppm |

Outputs

Output signal terminal CO₂ ³

| | |
|------------------------------------|--|
| OUT1 linear conversion range | 0 -10 VDC for 0 - 2 000 ppm. |
| OUT2 linear conversion range | 2 – 10 VDC, or 4 - 20 mA for 0 - 2 000 ppm. |
| D/A resolution..... | 10 bits, 10 mV |
| D/A conversion accuracy | ± 2 % of reading ± 50 mV |
| Electrical characteristics..... | R _{OUT} < 100 Ohm, R _{LOAD} > 5 kOhm |

Resistive terminals ⁴

| | |
|--------------------------|---|
| Thermistor outputs | temperature measurement resistor terminal output with signal return connected to ground terminal (option -Tr) |
|--------------------------|---|

Housing option

eSENSE II: Dim.: 130 x 85 x 30 mm (H x W x D)
Protection class: IP30
With or without display

Fits US standard J-boxes.



Note 1: The SO₂ enriched environments are excluded.

Note 2: In normal IAQ applications (@ NTP). Accuracy is defined after minimum 3 weeks of continuous operation. The tolerance of the span calibration gas (2 % unless otherwise requested) and test gas adds to the total uncertainty.

Note 3: The specifications are valid for the output load connected to ground G0. Other outputs and measurement ranges are available per request.

Note 4: Resistive probe is to be mounted by the user. Can be factory pre-mounted upon request.